

Residential Power Washers

Power Washers



2500 psi - Model 006595-0 (49-State & Canada)
UPC: 696471065954

2800 psi - Model 006596-0 (49-State & Canada)
UPC: 696471065961

Model 006597-0 (50-State)
UPC: 696471065978

3100 psi - Model 006598-0 (49-State & Canada)
UPC: 696471065985

Model 006599-0 (50-State)
UPC: 696471065992



*Built in the USA using domestic and foreign parts

FEATURES

POWERFUL GENERAC OHV ENGINE

- Delivers maximum cleaning performance and reliability

AXIAL CAM PUMP WITH EASY-ACCESS HOSE CONNECTIONS

- Prevents kneeling down on the ground

ERGONOMIC SPRAY GUN

- Molded grip, easier-to-pull trigger, and rear hose connection for comfort during prolonged use

OVERSIZED NEVER-FLAT TIRES

- Improved mobility on rugged terrain

QUICK CLICK NOZZLE TIPS

- Easily change the intensity of the spray to suit the application

COMPACT DESIGN

- Minimum storage space required in the garage or shed

2500 • 2800 • 3100 psi
specifications
PRESSURE AND FLOW

Max Outlet Pressure (psi/bar)	2500/172 - 006595-0 2800/193 - 006596-0 & 006597-0 3100/213 - 006598-0 & 006599-0
Max Flow Rate (gpm)/(L/min)	2.3/8.7 - 2500 psi 2.5/9.5 - 2800 psi 2.7/10.2 - 3100 psi

ENGINE

Manufacturer	Generac
Displacement (in ³ /cc)	11.9/196 - 2500 & 2800 psi 12.9/212 - 3100 psi
Type	OHV (Overhead Valve)
Orientation	Horizontal
Low Oil Shutdown System	No
Fuel Capacity (qt/L)	0.8/3
Fuel On/Off Switch	Yes
Oil Capacity (oz/L)	20/0.6
Recommended Engine Oil	SAE 30 or 10W30
Throttle Control	Fixed Speed
Choke	Manual
Starting Method	Manual/Recoil

PUMP

Type	Axial cam
Maximum Water Supply Temperature (°F/°C)	100/38

HOSE

Length (ft/m)	25/7.6 - 2500 & 2800 psi 30/9.1 - 3100 psi
Diameter (in/mm)	.25/6.4
Rating (psi/bar)	3100/214
Connectors	M22 threaded

DETERGENT SYSTEM

Number of Chemical Tanks per Unit	0 - 2500 psi 1 - 2800 psi 2 - 3100 psi
Chemical Tank Description	Siphon hose - 2500 psi 3/4 gallon (2.8 liters) - 2800 & 3100 psi

NOZZLES

Number of Nozzles per Unit	3 - 2500 psi 4 - 2800 psi 5 - 3100 psi
Nozzle Descriptions	0, 25, soap - 2500 psi 0, 25, 40, soap - 2800 psi 0, 15, 25, 40, soap - 3100 psi

GUN & LANCE

Gun Type	Ergonomic - 2500 & 2800 psi High Performance - 3100 psi
Gun to Lance Connection	M22 Threaded
Gun to Hose Connection	M22 Threaded
Lance Length (in/cm)	20/51
Lance to Nozzle Connection	Quick change

FRAME & MISC.

Handle	Fixed - Click in
Frame Construction	Welded steel
Wheels (in/cm)	1.75 x 10/3.8 x 25.4 Never flat

DIMENSIONS & WEIGHTS

Length (in/cm)	23.25/59.1
Width (wheel to wheel, in/cm)	16/40.6
Height (in/cm)	40.25/102.2
Unit Weight (lbs/kg)	60.3/27.4 - 2500 psi 61.5/27.9 - 2800 psi 67.5/30.6 - 3100 psi
Boxed Length (in/cm)	27/69.5
Boxed Width (in/cm)	18/45.7
Boxed Height (in/cm)	21/53.3
Boxed Weight (lb/kg)	68/30.8 - 2500 psi 69/31.3 - 2800 psi 74/33.6 - 3100 psi

WARRANTY

Warranty	2 year limited
----------	----------------